


CITIBUS

TECHNICAL SPECIFICATIONS

Dimensions (mm)			
Maximum Length	9515		
Maximum Width	2409		
Maximum Height	3117 (w A/C)		
Wheelbase	4435		
Front Overhang	2135		
Rear Overhang	2945		
Weights (kg)			
Gross Vehicle Weight	14050		
Engine			
Model	Cummins B4.5E6E210B		
Туре	Commonrail Turbo Diesel Intercooler		
Number of Cylinders	4		
Displacement (cc)	4500		
Maximum Power (kW(PS)/rpm)	151 (206) / 2300		
Maximum Torque (Nm/rpm)	832 /1200-1450		
Emission Standard	Euro VI OBD-E		
Transmission			
Model	Allison T 280 R		
Number of Gears	6 Forward, 1 Reverse		
Steering System	Hydraulic		
Tyres —			
Tyre Sizes	265/70 R19,5		
Suspension			
Front	Independent Air Suspension - 2 Air Bellows		
Rear	Air suspension - 4 bellows		
Anti Roll Bar	S		
Kneeling System (ECAS & ELC)	S		
Brake System			
Front / Rear	Disc / Disc		
System	Full Air Brake System with EBS and ABS,		
	Dual Circuit, Auto-Adjusted		
Parking Brake	Air Actuated, Acted on the Rear Axle		
Auxiliary Brake	Retarder		
Fuel Tank	0.4.5		
Fuel Tank Capacity (lt)	215		
Adblue Tank (lt)	30		
Electrical System	0/1//0//401/) 450 41		
Battery	24V (2X12V) - 150 Ah		
Passenger Capacity*	74		
Maximum Passenger Capacity Standard Layout	25 Seated (1 Foldable Seat) + 43 Standing		
	29 Seated + 42 Standing		
Optional Seat Layouts Standard Layout with Wheelchair	29 Seated + 42 Standing 18 Seated + 1 Wheelchair + 49 Standing		







FOUIPMENTS

EUUIPMENIS		
Heating and Ventilation		
Pre Heater	Opt	
Fan Heater (Front/Middle/Rear)	5	
Air Conditioner		
Digital Air Conditioner		
A/C Dashboard Nozzle Diffuser for Driver Tropical A/C	S Opt	
Safety & Driving Comfort	General Safety Regulation	
Tachograph	S LDWS	Opt
ASR	S Blind Spot Information System (BSIS)	S
EBD	S Moving Off Information System (MOIS)	S
Bus Stop Brake (BSB)	S Intelligent Speed Asistance (ISA)	S
Hillholder	Tyre Pressure Monitoring System (TPMS)	
Retarder	Intelligent Speed Asistance (ISA) Tyre Pressure Monitoring System (TPMS) Alcohol Interlock Installation Driver Drowsiness and Attention Warning Cyber Security and Cyber Security Manag Reversing Motion (RM) Emprengacy Stop Signal (ESS)	S (Preperation a (DDAW)
Spare Wheel	Cyber Security and Cyber Security Manag	
Tyre Inflation Set	Reversing Motion (RM)	S
Roof Hatch for Ventilation & Emergency Exit	Emergency Stop Signal (ESS)	· ·
Reverse Gear Warning Beeper	5 FRS	S
Fire Extinguisher Engine Compartment Fire Detection	S Passive Lane Change	Opt
and Automatic Fire Supression System	S	
Fog Lamps	S (Front / Rear)	
Locking System		
Battery Main Switch	S S S	
Third Stop Lamp	S	
Exterior		
Metallic Paint	Opt	
Towing Device	5	
Side Stripe Sticker	Opt	
Doors —		
Number of Service Doors	B Doors (S), 2 Doors (Opt)	
Type of Service Doors	Front, Rear: Single Wing, Pneumatic, Inward Swi	ina
	Middle: Double Wings, Pneumatic, Inward Swing	
Wheelchair / Strollers Ramp	S (Middle Door With Sensor)	,
Windows —		
Passenger Windows	One Piece 1/3 Sliding Window on Each Side,	
	Single Glazed (S), Double Glazed (Opt)	
Front Door Window	Double Glazed (S)	
Driver's Window	Sliding, Single Glazed With Heater (S)	
Interior		
Driver Compartment —		
Driver's Seat	Ergonomic, Air Operated, Adjustable	
Electrically Controlled and Heated Side Mirrors	Heated (S), Electrically Controlled (Opt)	
Ticket Validator Preperation	Opt	
Blind	Windshield Blind (S), Driver Curtain (Opt)	
Passenger Compartment	(-), (-),	
Backrest (for Standing Passengers)	5	
Lightening & Signalization —		
Interior Ceiling Lighting	S	
Stop Buttons & Signboard	S	
Digital Destination Display	Front, Rear (S)	
Audio & Visual		
Camera Systems	Opt	
Camera Monitor on Dashboard	Opt	
Recording Device (DVR)	Opt	
Radio System	Radio, USB, MP3, SD Card	
Monitor / LCD Screen (Passenger Compartment)	Opt	
Digital Clock	Opt	
Driver Speaker	S	
Announcement System for Passenger Area	Opt	

