



ISUZU CITI PORT 18 CNG

Manufactured by Anadolu Isuzu
The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

ISUZU CITIPOINT 18 CNG

TECHNICAL SPECIFICATIONS

Dimensions (mm)

Maximum Length	18200
Maximum Width	2550
Maximum Height	3400
Wheelbase 1,2	5850, 6170
Front Overhang	2700
Rear Overhang	3480

Weights (kg)

Gross Vehicle Weight	29000
----------------------	-------

Engine

Model	Cummins L9NE6E320
Type	CNG Turbocharged
Number of Cylinders	6
Displacement (cc)	8880
Maximum Power (kw(PS)/rpm)	235 (320) / 2000
Maximum Torque (Nm/rpm)	1357 / 1300-1400
Emission Standard	Euro VI OBD-E

Transmission

Model	ZF 6AP 1400 EMF
Number of Gears	6 Forward, 1 Reverse

Steering System

Hydraulic and Adjustable Dashboard and Steering Wheel Column in Height and Inclination

Tyres

Tyre Sizes	275/70 R22,5
------------	--------------

Suspension

Front	Air Suspension - 2 Bellows Independent Suspension Electronically Controlled (ECAS)
Middle, Rear	Air Suspension - 4 Bellows Electronically Controlled (ECAS)
Anti Roll Bar	S
Kneeling System (ECAS)	S

Brake System

Front, Middle, Rear System	Disc / Disc / Disc Full Air Brake System With EBS (Automatic Oil, Water Separator System is Optional)
Parking Brake	Air Actuated Acted on Rear Axle
Auxiliary Brake	Intarder

Fuel Tank

Gas Tanks Capacity (L)	5 x 320 lt (1600 lt) - Type 3 CNG (NGV1&NGV2)
------------------------	---

Electrical System

Battery	24V (2x12V) - 240 Ah
---------	----------------------

Passenger Capacity*

Maximum Passenger Capacity	144
Standard Layout	41 Seated + 103 Standing
Layout with Wheelchair	41 Seated + 2 Wheelchair + 92 Standing



EQUIPMENTS

Heating and Ventilation

Pre Heater	Opt
Air Conditioner	
Digital Air Conditioner	S
A/C With Heater	Opt

Safety & Driving Comfort

Speed Limitor	S
Tachograph	S
Multiplex System	S
ABS	S
ASR	S
EBS	S
EBD	S
Bus Stop Brake (BSB)	S
Hillholder	S
Retarder	S
Parking Sensor	S
Spare Wheel	S
Tyre Inflation Set	S
Roof Hatch for Ventilation & Emergency Exit	S
Reverse Gear Warning Beeper	S
Fire Extinguisher	S
Engine Compartment Fire Detection and Automatic Fire Supression System	S
Fog Lamps	S (Front / Rear)
Day Time Running Lamps (DRL)	S
Locking System	S
Battery Main Switch	S

Exterior

Metallic Paint	Opt
Side Stripe Stickers	Opt
Towing Device	S

Doors

Number of Service Doors	4 Doors (S), 3 Doors (Opt)
Type of Service Doors	DoubleWing Air Actuated Interior Movement for All Front, Middle and Rear Doors
Wheelchair Ramp	Manual with Sensor
Remote Control	S (Front Service Door)

Windows

Type	Non-sliding, 1/4 Hinged Passenger Windows, Single Piece (S), With Slider, Double Piece (Opt)
Driver Window	Single Glazed (S), Double Glazed (Opt)
Layers of Glass	Single Glazed (S), Double Glazed (Opt)

Interior

Driver Seat

Driver's Seat	Air Actuated, Adjustable
Steering	Adjustable Steering Wheel
Side Mirrors	Electrically Controlled, Heated
Driver's Cabin	Semi Glass (S), Full Glass (Opt)
Driver Overhead Cabinet	S
Coathanger for The Driver	S
Ticket Validator Preparation	Opt

Passenger Compartment

Passenger Seat Material	Cloth Ped On Plastic
USB Charger for Passangers	S

Lightening & Signalization

Interior Ceiling Lighting	S (Continuous type with LED)
Stop Buttons & Signboard	S
Digital Destination Display	Front, Rear (S), Colored (Opt)

Audio & Visual

Camera Systems	S
Camera Monitor on Dashboard	S
Recording Device (DVR)	S
Radio System	Radio, USB, MP3
Monitor / LCD Screen (Passenger Compartment)	S
Digital Clock	S
Wifi Preparation	S
Driver Speaker	S
Announcement System for Passenger Area	Opt

S: Standard **Opt:** Optional

* Different seating variations are available.

